

MATERIAL SAFETY DATA SHEET
Essentially Similar to U.S. Department of Labor Form OSHA
Revised: 01/20/12
HMIS Health-1 Flammability-3 Reactivity 0
SECTION I-Product Information

4/9/2019

Manufacturer: A.V.W. Inc.
24 Hour Emergency Phone Number: 800-424-9300
Product Name: Blow Off Rubber Rejuvenator

SECTION II-Hazardous Ingredients

Xylene	CAS#	95-47-6	TWA	100
Methanol	CAS#	67-56-1	TWA	200
Mineral Spirit	CAS#	8052-41-3	TWA	200
Acetone	CAS#	67-64-1	TWA	1000
Isopropanol	CAS#	6763-0	TWA	400
Propane	CAS#	74-98-6	TWA	1000
Butane	CAS#	106-97-8	TWA	800

Blow OFF
Rubber Rejuvenator
Cleans & Restores
Rubber Rollers

SECTION III-Physical Data

Boiling Point: 188 F
Specific Gravity (H2O=1): .86
Solubility in Water: .0%
Appearance: Colorless liquid with penetrating ether like odor.

SECTION IV-Fire and Explosion Hazard Data

Flash Point: 98 F Extremely Flammable Level 3 Aerosol
Extinguishing Media: Water, CO2, Foam, Dry Chemical
Special Fire Fighting Procedures: Do not expose containers to temperatures above 120 F.
Unusual Fire and Explosion: Forms flammable vapor air mixtures. Lower temperatures increase the difficulty of getting it to ignite.

SECTION V-Health Hazard and First Aid

Time Weighted Average (TWA): 100 ppm based in the raw material.
Carcinogen: No
Acute Chronic Health Effects: Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may cause carboxyhemoglobinemia, thereby impairing the bloods ability to transport oxygen.
Primary Routes of Entry: X Inhalation X Skin X Ingestion
Effects of Overexposure: Eyes- May cause pain, moderate eye irritation and slight corneal injury. Vapors may irritate eyes.
Skin- May cause irritation. Repeated contact may cause drying or flaking of the skin.
Inhalation- In confined or poorly ventilated areas, vapors can readily accumulate and cause unconsciousness and death.
Ingestion- May be harmful.
First Aid: Eyes- Flush with water for 15 minutes. If irritation persists get medical attention.
Skin- Wash with soap and water.
Inhalation- Move to fresh air. Get medical attention.
Ingestion- Do not induce vomiting. Get medical attention immediately.

SECTION VI-Reactivity Data

Stability: Stable X
Conditions to Avoid: Hydrolysis producing small amounts of hydrochloric acid possible with gross water contamination. Avoid open flames, welding arcs, or other high temperature sources, which induce thermal decomposition.
Incompatibility: Strong oxidizers; caustics, chemically active metals such as aluminum, magnesium and sodium.

SECTION VII-Spill or Leak Procedures

Steps to take in case material is spilled or released: Use absorbent material and trash receptacle. Waste disposal method Federal and Local regulations.

SECTION VIII-Special Protection Information

Respiratory Protection: Adequate ventilation
Gloves (type): Chemical resistant
Eye Protection: Glasses (if required)
Other Protective Equipment: None

SECTION IX-Special Precautions

Precautions to be taken in handling and storing: Read and follow all label directions. Do not store containers at temperatures above 120 F.

SECTION X- WHMIS CLASSIFICATION

WHMIS Class B -Flammable and Combustible Material
Division 5- Flammable Aerosol