

12/2/2011

STANLEY-BOSTITCH -- BC602 PNEUMATIC TOOL LUBRICANTS -- 9150-00F025510

=====
Product Identification
=====

Product ID:BC602 PNEUMATIC TOOL LUBRICANTS
MSDS Date:01/01/1991
FSC:9150
NIIN:00F025510
MSDS Number: BPSCW
=== Responsible Party ===
Company Name:STANLEY-BOSTITCH
Address:ROUTE 2
City:EAST GREENWICH
State:RI
ZIP:02818
Country:US
Info Phone Num:401-884-2500
Emergency Phone Num:401-884-2500
CAGE:0E7F8

Bostitch Stanley
Pneumatic Tool
Lubricant

=====
Contractor Identification
=====

Company Name:STANLEY-BOSTITCH
Address:ROUTE 2
Box:City:EAST GREENWICH
State:RI
ZIP:02818
Country:US
Phone:401-884-2500
CAGE:0E7F8

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY
PARAFFINIC, LUBRICATING OIL BASE STOCK
CAS:64741-88-4
RTECS #:PY8040500
OSHA PEL:5 MG/CUM
ACGIH TLV:5 MG/CUM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:
LUNG IRRITATION.
Explanation of Carcinogenicity:NONE

=====
First Aid Measures
=====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR
15 MIN. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE
VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:141C/285F
Lower Limits:1%
Upper Limits:6%
Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT SPREAD OF SPILL, ABSORB W/SAND OR
INERT MATERIALS, SWEEP OR SCOOP UP & REMOVE.

===== Handling and Storage =====

Handling and Storage Precautions:USE METHODS GENERALLY ADVOCATED FOR
PETROLEUM PRODUCTS. DON'T MIX W/OXIDIZING MATERIALS.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W/SKIN,
INHALATION OF FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS REQUIRED

Ventilation:LOCAL EXHAUST

Protective Gloves:RECOMMENDED

Eye Protection:GOGGLES

Other Protective Equipment:APRON

Work Hygienic Practices:DON'T WEAR CONTAMINATED CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:<0.01

Vapor Density:>12

Spec Gravity:0.875

Evaporation Rate & Reference:(BU AC = 1): <0.01

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PALE CLEAR LIQUID, PETROLEUM ODOR.

Percent Volatiles by Volume:NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.