

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 11/09/2016

Revision date: 06/26/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name

: PB Penetrating Catalyst

Product code

: 16-PB, 8-PB, 8-PBS, PB-TS, 20-PB, 26-PB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

: Penetrant

1.3. Details of the supplier of the safety data sheet

Manufacturer

The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T (216) 901-5800 - F (216) 901-5801 www.blastercorp.com

Blaster Work It Like A PND PB Penetrating Cafalyst

1.4. Emergency telephone number

Emergency number

: ChemTel 800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2

Dissolved gas

Asp. Tox. 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS04



Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways.

Precautionary statements (GHS-US)

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local, regional,

national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

.2			res

Name A	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	50 - 60
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	20 - 30
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	20 - 30
Carbon dioxide	(CAS No) 124-38-9	1 - 4

SECTION 4: First aid measures

4.1.		aid measures

First-aid measures after inhalation

- : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact

: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion

IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce

vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

- : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact
- May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the
- Symptoms/injuries after eye contact
- May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear
- production, with possible redness and swelling.
- Symptoms/injuries after ingestion
- May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and
 - cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

- : Carbon dioxide, dry chemical, halons or foam.
- Suitable extinguishing media Unsuitable extinguishing media
- : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard

Reactivity

: Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon and oxides of nitrogen.

Explosion hazard

Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

: No dangerous reaction known under conditions of normal use.

Advice for firefighters

Firefighting instructions

- : DO NOT fight fire when fire reaches explosives, Evacuate area. Exercise caution when fighting any chemical fire.
- Protection during firefighting
- Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

- : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.
- 6.1.1. For non-emergency personnel

Emergency procedures

Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection.

2/7 06/26/2017 EN (English)



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Emergency procedures

: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter

waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapour or spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/

122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place.

Storage area

: Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)

Not applicable

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)

Not applicable

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

Not applicable

Carbon dioxide (124-38-9)				
ACGIH	ACGIH TWA (ppm)	5000 ppm		
ACGIH	ACGIH STEL (ppm)	30000 ppm		
OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³		
OSHA	OSHA PEL (TWA) (ppm)	5000 ppm		

8.2. Exposure controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection

: Wear chemically resistant protective gloves.

Eye protection

: Safety glasses or goggles are recommended when using product.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls

: Maintain levels below Community environmental protection thresholds.

Other information

: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and

safety practices.



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

: Liquid

Appearance

: Clear. Aerosol.

Colour

Orange

Odour

Odour threshold

Characteristic

: No data available

pН

No data available

Melting point

No data available

Freezing point

: No data available

Boiling point

356 °F (180 °C)

Flash point

: > 141 °F (> 61 °C)

Relative evaporation rate (butylacetate=1)

No data available

Flammability (solid, gas)

: Flammable aerosol.

Vapour pressure

: No data available

Relative vapour density at 20 °C

No data available

Relative density

: 0.9

Solubility

No data available

Partition coefficient n-octanol/water

No data available

Auto-ignition temperature

No data available

Decomposition temperature

No data available

Viscosity, kinematic

No data available

Viscosity, dynamic

No data available

Explosive limits

No data available

Explosive properties

: No data available No data available

Oxidising properties

9.2. Other information

Heat of Combustion

: 45.8 kJ/g

Flame Projection

: 0 inches

Flashback

None

SECTION 10: Stability and reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon and oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Not classified.

06/26/2017

EN (English)

4/7



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

PB Penetreating Catalyst			
LD50 oral rat	> 2000 mg/kg (Calculated Acute Toxicity Estimate)		
LD50 dermal rabbit	> 2000 mg/kg (Calculated Acute Toxicity Estimate)		
LC50 inhalation rat	> 5 mg/l/4h (Calculated Acute Toxicity Estimate)		
Petroleum distillates, hydrotreated light (64	742-47-8)		
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	> 5.2 mg/l/4h		
Solvent naphtha, petroleum, heavy aromati	c (64742-94-5)		
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 2 ml/kg		
LC50 inhalation rat	> 590 mg/m³ (Exposure time: 4 h)		
Skin corrosion/irritation	: Not classified.		
Serious eye damage/irritation	: Not classified.		
Respiratory or skin sensitisation	: Not classified.		
Germ cell mutagenicity	: Not classified.		
Carcinogenicity	: Not classified.		
Reproductive toxicity	: Not classified.		
Specific target organ toxicity (single exposure)	: Not classified,		
Specific target organ toxicity (repeated exposure)	: Not classified.		
Aspiration hazard	: May be fatal if swallowed and enters airways.		
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.		
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.		
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.		
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.		
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.		

SECTION 12: Ecological information

Ass.	Tox	

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotre	ated light (64742-47-8)			
LC50 fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])			
Solvent naphtha, petroleum, h	eavy aromatic (64742-94-5)			
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)			
Distillates, petroleum, hydrotre	ated heavy naphthenic (64742-52-5)			
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)			
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)			

12.2. Persistence and degradability



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.3. Bioaccumulative potential	
PB Penetreating Catalyst	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light	(64742-47-8)
BCF fish 1	61 - 159
Solvent naphtha, petroleum, heavy aron	natic (64742-94-5)
BCF fish 1	61 - 159
Partition coefficient n-octanol/water	2.9 - 6.1
Carbon dloxide (124-38-9)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming

: No known effects from this product.

Other information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description

: UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT)

: UN1950

Proper Shipping Name (DOT)

: Aerosols

flammable, (each not exceeding 1 L capacity)

Class (DOT)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT)

2.1 - Flammable gas



Other information

: No supplementary information available.

Special transport precautions

: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Naphthalene (91-20-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	5.8 μg/day

Carbon dloxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Date of issue

: 11/09/2016

Revision date

: 06/26/2017

Other information

: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

